

1" ALUMINUM MINI BLIND SPECIFICATION

- Manufacturer:** HT Window Fashions, City of Industry, California USA
- Steel Head Rail:** Standard headrail is 1" high by 1-1/8" U shaped channel. Phosphate coated vinyl primered finished with a polyester baked enamel. HT also offers 1" high by 1-1/2" integrated headrail.
- Bottom Rail:** C shaped rail, phosphate coated and vinyl primered finished with a polyester baked enamel
- Slats:** Cold rolled spring tempered virgin aluminum slat. To have normal width of 1" and be 0.006" thickness after paint, to provide maximum strength and flexibility. Slats to be finished with a polyester baked enamel. Slat with 0.008" thickness after paint is available too.
- Tilter:** The tilter shall be worm gear design and shall be in an enclosed housing and secured by means of steel rivets to prevent separation. The stem shall be made of clear polycarbonate, the gear of polyacetal and the housing of clear polycarbonate, prelubed prior to assembly to assure durability and ease of use.
- Tilt Wand:** Tilt wand should be plastic measuring approximately 5/16", fluted with grooves for non slip grip.
- Cord Lock:** Cord lock shall be secured to the head rail channel by means of steel pins to prevent dislodgement. Lock body shall be constructed of clear polycarbonate, floating gear and lock pins shall be made of brass. Cord lock to be of crash- proof design.
- Valance:** Double slat with clips to mount to 1" headrail. No valance required for 1-1/2" headrail.
- Tilt Drums:** Shall be polyacetal with steel tape fasteners to secure ladders to head rail
- Drum Supports:** Constructed of polypropylene with steel cord pin to reduce friction.
- Ladders:** Braided polyester with spacing of not more than 0.865" and arranged for total support of slat.
- Tilt Rod:** "D" shaped and galvanized to prevent corrosion.
- Lift Cord:** Shall be braided polyester and of sufficient length to control the raising and lowering of the blind.
- Installation Bracket:** Standard hidden brackets. Zine plated to prevent corrosion. Box bracket with hinged door is also available. Constructed of cold rolled steel. Finished with polyester baked enamel. Coating to match color of blind.
- Tassel:** Shall comply with all safety requirements.
- Fire Safety:** Blind materials have been tested in accordance with the procedures outlined in NFPA 701 Fire Test 1.

HT 1" mini blind manufacturing division is assessed and registered as meeting the requirements and the high quality standards of the ISO 9002 certification.

For detailed information, please contact HT custom service.

770 South Epperson Drive, City of Industry, CA 91748

Phone: (626) 839-8866 (800) 879-9512

Fax: (626) 839-8861